





Mounting Adapter YD

THREADED MOUNTING ADAPTER Material - stainless steel (see Appendix - Sheath materials) Application - with probes series TS, LC, PS, etc.	YDx	DIMENSIONS *				
		E	SW	K1 [mm]	N	d _{max} [mm]
STANDARD M/M DESIGN (1) 		M10x1(1.5); G1/8"	17	9	M8 / M10 / M12 G1/8" / 1/8" NPT	5 / 6 / 6 9 / 10 5 / 5
		1/8" NPT; M12x1.5		10		
		M14x1.5; G1/4"	19	12	as above; M14 / G1/4" / 1/4" NPT	as above; 12 / 12 / 15 8 / 6 / 6
		1/4" NPT		15		
		M16x1.5; G3/8"	22	13	as above; M16 / G3/8" / 3/8" NPT	as above; 13 / 13 / 15 10 / 10 / 10
		3/8" NPT		15		
		M18x1.5	24	13	as above; M18x1.5	as above; 13 as above; 10
		M20x1.5; G1/2"	27	15	as above; M20 / G1/2" / 1/2" NPT	as above; 15 / 15 / 20 12
		1/2" NPT		20		
		M27x2; G3/4"	32	17	as above; M27 / G3/4" / 3/4" NPT	as above; 17 / 17 / 20 as above; 16
EXTENDED M/F DESIGN (2) 		M10x1(1.5); G1/8"	17	9	M8 / M10 / M12 / M14 G1/8"(NPT) / G1/4"(NPT)	6 / 6 / 8 / 10 8 / 11 6 / 8
		1/8" NPT; M12x1.5		10		
		M14x1.5; G1/4"	19	12	as above; M16 / G3/8" / 3/8" NPT	as above; 13 / 13 / 12 as above; 14
		1/4" NPT		15		
		M16x1.5; G3/8"	22	13	as above; M18	as above; 14
		3/8" NPT		15		
		M18x1.5	24	13	as above; M20 / G1/2"(NPT)	as above; 15 / 15 as above; 16
		M20x1.5; G1/2"	27	15		
		1/2" NPT		20		
		M27x2; G3/4"	32	17	as above; M27 / G3/4" / 3/4" NPT	as above; 17 / 17 / 16 as above; 20
LOW-PROFILE M/F DESIGN (3) 		M16x1.5; G3/8"	22	13	M8 / M10 / M12 G1/8"(NPT) / G1/4"(NPT)	6 / 6 / 8 8 / 11 6 / 8
		3/8" NPT		15		
		M18x1.5	24	13	as above; M14	as above; 12 as above; 10
		M20x1.5; G1/2"	27	15	as above; M16 / G3/8" / 3/8" NPT	as above; 13 / 13 / 12 12 / 12 / 12
		1/2" NPT		20		
		M27x2; G3/4"	32	17	as above; M18 / M20 / G1/2"(NPT)	as above; 14 / 15 / 15 as above; 14
		3/4" NPT		20		
		M33x2; G1"	36	19	as above; M27 / G3/4" / 3/4" NPT	as above; 17 / 17 / 16 as above; 20
		1" NPT		25		
					Maximum temperature: 850 °C Maximum pressure: 40 bar * Other dimensions are available on request. Please contact COMECO!	
GLAND-TYPE DESIGN (4)  DN = d		M16x1.5; G3/8"	22	13	N and SW1 are specified by the manufacturer	3...8
		3/8" NPT		15		
		M18x1.5	24	13		
		M20x1.5; G1/2"	27	15		3...8 4...12
		1/2" NPT		20		
		M27x2; G3/4"	32	17		4...12 6...16
		3/4" NPT		20		
		M33x2; G1"	36	19		6...16 8...20
		1" NPT		25		
					Maximum temperature: dependant on ferrule material Maximum pressure: 6(10) bar * Other dimensions are available on request. Please contact COMECO!	

Ordering code YD★ - G4.G9'G9".G10'G10"

Code	Feature or option	Code values
★	Design	1 - standard m/m, 2 - extended m/f, 3 - low-profile m/f, 4 - gland-type
G4	Probe diameter 'd' [mm] ⁽¹⁾	1.5, 2, 3, 4, 4.5, 5, 6, 8, 10, 12, 14, 16, 20
G9'	Connection thread 'E' ⁽¹⁾	X - none ⁽⁴⁾ , Q0 - M16x1.5, Q1 - M18x1.5, Q2 - M20x1.5, Q3 - G3/8", Q4 - G1/2", Q5 - M27x2, Q6 - G3/4", Q7 - M12x1.5, Q8 - M14x1.5, Q9 - 3/8" NPT, Q10 - 1/2" NPT, Q11 - 3/4" NPT, Q12 - G1", Q15 - 1" NPT, Q18 - G1/8", Q19 - 1/8" NPT, Q20 - M10x1, Q23 - G1/4", Q24 - 1/4" NPT, Q25 - M33x2, Q30 - M10x1.5, Z - other (specify!)
G9"	Probe thread 'N' ^(1,2)	X - none ⁽⁴⁾ , Q0/U0 - M16x1.5, Q1/U1 - M18x1.5, Q2/U2 - M20x1.5, Q3/U3 - G3/8", Q4/U4 - G1/2", Q5/U5 - M27x2, Q6/U6 - G3/4", Q7/U7 - M12x1.5, Q8/U8 - M14x1.5, Q9/U9 - 3/8" NPT, Q10/U10 - 1/2" NPT, Q11/U11 - 3/4" NPT, Q12/U12 - G1", Q15/U15 - 1" NPT, Q18/U18 - G1/8", Q19/U19 - 1/8" NPT, Q20/U20 - M10x1, Q23/U23 - G1/4", Q24/U24 - 1/4" NPT, Q25/U25 - M33x2, Q26/U26 - M8x1, Q29/U29 - M8x1.25, Q30/U30 - M10x1.5, Z - other (specify!)
G10'	Material	M1 - 1.4301, M2 - 1.4541 ⁽⁴⁾ , M3 - 1.4571 ⁽⁴⁾ , M9 - 1.4404 or 1.4435, Z - other (specify!) ⁽⁴⁾
G10"	Compression fitting ferrule ⁽³⁾	TF - Teflon®, BR - brass, SS - stainless steel





⁽¹⁾ Applicable for the selected design

⁽²⁾ Omit for YD4!

⁽³⁾ Only for YD4!

⁽⁴⁾ Contact COMECO!

Монтажен адаптер YD

РЕЗБОВИ МОНТАЖЕН АДАПТЕР		YDx	РАЗМЕРИ *					
Материал - неръждаема стомана (виж Приложение - материали за корпуси) Приложение - при сонди TS, LC, PS и др.			E	SW	K1 [mm]	N	H2 [mm]	d _{max} [mm]
СТАНДАРТЕН М/М МОДЕЛ (1) 			M10x1(1.5); G1/8"	17	9	M8 / M10 / M12 G1/8" / 1/8" NPT	8 / 9 / 10 9 / 10	5 / 6 / 6 5 / 5
			1/8" NPT; M12x1.5		10			
			M14x1.5; G1/4"	19	12	като горните; M14 / G1/4" / 1/4" NPT	като горните; 12 / 12 / 15	като горните; 8 / 6 / 6
			1/4" NPT		15			
			M16x1.5; G3/8"	22	13	като горните; M16 / G3/8" / 3/8" NPT	като горните; 13 / 13 / 15	като горните; 10 / 10 / 10
			3/8" NPT		15			
			M18x1.5	24	13	като горните; M18x1.5	като горните; 13	като горните; 10
			M20x1.5; G1/2"	27	15	като горните; M20 / G1/2" / 1/2" NPT	като горните; 15 / 15 / 20	като горните; 12
			1/2" NPT		20			
			M27x2; G3/4"	32	17	като горните; M27 / G3/4" / 3/4" NPT	като горните; 17 / 17 / 20	като горните; 16
3/4" NPT	20							
M33x2; G1"	36	19	като горните; M33 / G1" / 1" NPT	като горните; 19 / 19 / 25	като горните; 20			
1" NPT		25						
УДЪЛЖЕН М/Ж МОДЕЛ (2) 			M10x1(1.5); G1/8"	17	9	M8 / M10 / M12 / M14 G1/8"(NPT) / G1/4"(NPT)	8 / 9 / 10 / 12 8 / 11	6 / 6 / 8 / 10 6 / 8
			1/8" NPT; M12X1.5		10			
			M14x1.5; G1/4"	19	12	като горните; M16 / G3/8" / 3/8" NPT	като горните; 13 / 13 / 12	като горните; 12 / 12 / 12
			1/4" NPT		15			
			M16x1.5; G3/8"	22	13	като горните; M18	като горните; 14	като горните; 14
			3/8" NPT		15			
			M18x1.5	24	13	като горните; M20 / G1/2"(NPT)	като горните; 15 / 15	като горните; 16 / 16
			M20x1.5; G1/2"	27	15			
			1/2" NPT		20			
			M27x2; G3/4"	32	17	като горните; M27 / G3/4" / 3/4" NPT	като горните; 17 / 17 / 16	като горните; 20 / 20 / 20
3/4" NPT	20							
M33x2; G1"	36	19	като горните; M33 / G1" / 1" NPT	като горните; 19 / 19 / 18	като горните; 20 / 20 / 20			
1" NPT		25						
СКЪСЕН М/Ж МОДЕЛ (3) 			M16x1.5; G3/8"	22	13	M8 / M10 / M12 G1/8"(NPT) / G1/4"(NPT)	8 / 9 / 10 8 / 11	6 / 6 / 8 6 / 8
			3/8" NPT		15			
			M18x1.5	24	13	като горните; M14	като горните; 12	като горните; 10
			M20x1.5; G1/2"	27	15	като горните; M16 / G3/8" / 3/8" NPT	като горните; 13 / 13 / 12	като горните; 12 / 12 / 12
			1/2" NPT		20			
			M27x2; G3/4"	32	17	като горните; M18 / M20 / G1/2"(NPT)	като горните; 14 / 15 / 15	като горните; 14 / 16 / 16
			3/4" NPT		20			
			M33x2; G1"	36	19	като горните; M27 / G3/4" / 3/4" NPT	като горните; 17 / 17 / 16	като горните; 20 / 20 / 20
			1" NPT		25			
			Максимална температура: 850 °C Максимално налягане: 40 bar * Възможни са и други размери по заявка. Свържи се с КОМЕКО!					
МОДЕЛ С ЩУЦЕР (4)  DN = d			M16x1.5; G3/8"	22	13	N и SW1 се определят от производителя	3...8	
			3/8" NPT		15			
			M18x1.5	24	13			3...8 4...12
			M20x1.5; G1/2"	27	15			
			1/2" NPT		20			
			M27x2; G3/4"	32	17		4...12 6...16	
			3/4" NPT		20			
			M33x2; G1"	36	19		6...16 8...20	
			1" NPT		25			
Максимална температура: в зависимост от материала на втулката Максимално налягане: 6(10) bar * Възможни са и други размери по заявка. Свържи се с КОМЕКО!								

Код за поръчка YD★ - G4.G9'G9".G10'G10"

Код	Характеристика или опция	Стойност на кодвия символ
★	Модел	1 - стандартен м/м, 2 - удължен м/ж, 3 - скъсен м/ж, 4 - с щуцер
G4	Диаметър на сондата 'd' [mm] ⁽¹⁾	1.5, 2, 3, 4, 4.5, 5, 6, 8, 10, 12, 14, 16, 20
G9'	Присъединителна резба 'E' ⁽¹⁾	X - няма ⁽⁴⁾ , Q0 - M16x1.5, Q1 - M18x1.5, Q2 - M20x1.5, Q3 - G3/8", Q4 - G1/2", Q5 - M27x2, Q6 - G3/4", Q7 - M12x1.5, Q8 - M14x1.5, Q9 - 3/8" NPT, Q10 - 1/2" NPT, Q11 - 3/4" NPT, Q12 - G1", Q15 - 1" NPT, Q18 - G1/8", Q19 - 1/8" NPT, Q20 - M10x1, Q23 - G1/4", Q24 - 1/4" NPT, Q25 - M33x2, Q30 - M10x1.5, Z - друга (поясни!)
G9"	Резба на сондата 'N' ^(1,2)	X - няма ⁽⁴⁾ , Q0/U0 - M16x1.5, Q1/U1 - M18x1.5, Q2/U2 - M20x1.5, Q3/U3 - G3/8", Q4/U4 - G1/2", Q5/U5 - M27x2, Q6/U6 - G3/4", Q7/U7 - M12x1.5, Q8/U8 - M14x1.5, Q9/U9 - 3/8" NPT, Q10/U10 - 1/2" NPT, Q11/U11 - 3/4" NPT, Q12/U12 - G1", Q15/U15 - 1" NPT, Q18/U18 - G1/8", Q19/U19 - 1/8" NPT, Q20/U20 - M10x1, Q23/U23 - G1/4", Q24/U24 - 1/4" NPT, Q25/U25 - M33x2, Q26/U26 - M8x1, Q29/U29 - M8x1.25, Q30/U30 - M10x1.5, Z - друга (поясни!)
G10'	Материал	M1 - 1.4301, M2 - 1.4541 ⁽⁴⁾ , M3 - 1.4571 ⁽⁴⁾ , M9 - 1.4404 или 1.4435, Z - друг (поясни!) ⁽⁴⁾
G10"	Уплътнителна втулка ⁽³⁾	TF - Teflon®, BR - месинг, SS - неръждаема стомана

⁽¹⁾ От възможните за избрания модел

⁽²⁾ Пропусни при YD4!

⁽³⁾ Само за YD4!

⁽⁴⁾ Свържи се с КОМЕКО!